

V9 PET Preform Post-Mold Cooling System



Flexible and Saving

WETEC

W9 PET Preform Post-Mold Cooling System

Easy

Stable

Efficient

Universal

Save & Safe

Features

Standard layout

- Side Entry Robot (W920/W940/W960)
- EOAT (with water cooling)
- Vacuum pump
- Conveying unit
- The correct dimensions must be determined for each project. W920/W940/W960 are the models to meet the different product.
- PET moulds are available from us to meet customers' need for system integration.



Technical Specification

Entry stroke	1650mm (W920) / 1750 mm (W940)
Euromap interface	E12 / E67
Dimensions of system	2040 X 2060 mm (W920) / 2200 X 2100 mm (W940)
Controller	"Mobile commander with 8.4" TFT-LCD colorful touch panel."
	Easy operation / programming

Driven

Entry axis	Servo
EOAT	Servo
Power consumption	13 Kw / 60 A
Capacity	AC220V 3 ϕ 18KVA
Air consumption	5L / Cycle

The specifications are subject to change without notice.

WeTechnology Automation Co., Ltd.

No. 50, Hua Ya 1st. Rd., Gueishan,
Taoyuan, Taiwan

☎ +886 3 397 9588 ✉ sales2@wetec.com.tw
www.wetec.com.tw

Wetec Europe Otomasyon Tic.Ltd.Şti.

Barbaros Mh. Mor Sumbül Sk. Deluxia Palace D402,
Ataşehir 34746, İstanbul, Turkey

☎ +90 216 9990146
www.wetec.com.tr

Wetec Automation India Pvt. Ltd.

7, Raghav Industrial Park, S.P. Ring Road, Ramol,
Ahmedabad, India

☎ +91 9426766674